



X-Ray Baggage Scanner – Pro Series

Model No.: AT6040

Product Highlights:

- * Multilingual operation
- * Automatic built in test and self diagnosis
- * Secure access Key
- * Uninterruptable power supply (UPS)
- * Threat alert and material classification
- * Auto archiving
- * Network-Ready
- * Energy saving design
- * One key turn off
- * Drugs and explosives inspection
- * Indication of the date and time
- * baggage counter
- * Video Archive: Optional



General Specifications

Tunnel size(mm)	615(L)*418(W)
Conveyor Speed(m/s)	0.22
Conveyor height(mm)	680
Conveyor Max Load(kgs)	150
X ray dose per each inspection	Typical 2.0 μ Gy/h, guarantee 2.5 μ Gy/h
X ray leakage	Typical 1.0 μ Gy/h, guarantee 1.5 μ Gy/h
Penetration	Typical 32mm, guarantee 30mm
Wire Resolution	Typical AWG40, guarantee AWG38
Penetration Resolution	Typical AWG32, guarantee AWG30
Spatial resolution:	Typical dia1.0mm, Vertical: dia1.0mm; Guarantee dia1.3mm, Vertical: dia1.3mm;
Power Consumption	0.8KVA
Noise	< 60dB
Film Safety	Guarantee ASA/ISO1600 Film

Computer and other

Monitor	High Resolution Color, LCD Accord, 17inch
Hard Disk	SEAGATE 500G 3.5"
CPU	G1610 2.6G
Storage	2GB 1600MHz DDR3 Innodisk
Main board	H61 SYM76993VGGA



Image System	
X-ray Sensor	L-Shaped Photodiode Array (multi-energetic) , 12bit Deep
Image Display	High resolution of 1024 * 1280 pixel; Image Grey Level: 4096
Image Enhancement	1-64times enlargement continuity, Color/BW, negative, high/low penetration, organic /inorganic Stripping, general enhancement, and pseudo color, etc.
Image Recall	All preceding images recallable, retrieval
Explosives & Narcotics Detection	Explosives & narcotics alarm and highlight according to atomic number signature
High Density Region Alarm	Impenetrable region alarm and highlight, for possible concealing of threats and contrabands
Threat Image Projection	Inserting fictional, but realistic images of threat items into baggage during screening operation, for maintenance of vigilance, as well as training and assessment of image identification capability
Image Archive	Up to 100,000 images stored automatically, enable transferring to USB disk, and converting to JPG, BMP and other general formats
Miscellaneous Functions	Time/date display, counters, user management, system-on/X-ray-on timers, power on self test, built-in diagnostic facilities, dual-direction scanning, system log, system standby and stimulant training, ADS etc.
Network Applications	Multiple remote applications available based on Ethernet LAN and windows platform, such as image centralized storage and identify, recheck workstation, and network TIP, etc (Optional) .
Images process	24bit real time processing ,4colors analysis, Images displayed marked date and ID NO ,Count the number of bags

Operating Environment	
Operation temperature/Humidity	0°C-45°C / 5%-95%(non-condensing)
Storage Temperature/Humidity	-40°C to 70°C / 5%-95%(non-condensing)
Operation Power	220VAC(±10%) 50±3Hz (Optional: 100VAC,110VAC,120VAC,200VAC)
UPS	15mins, 30mins, 60mins etc, optional
Generate direct	from bottom to top
Cooling / Duty Cycle	Oil Cooling /100%



TARGET VISION SECURITY SYSTEMS

Regd Office:

11, Upper Ground Floor, New Gupta Colony
 Priyadarshini Vihar, Phase -1, Delhi - 110009.
 E-Mail: shashank@targetvisionindia.co.in
 www.targetvisionindia.co.in